

## Compressed air RH+T transmitter with RS485 output, cable 2 meters

code: T3419P-2



Humidity, temperature transmitter. T+RH probe from hard anodized duralumin for compressed air up to 25 bars on the cable. Outdoor, indoor use.

Humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy.

The device is supplied with T+RH probe with 2 meters cable.

### Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +105 °C
Accuracy	±0.4 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.5°C for dew point temperature +10°C and higher at ambient temperature +25°C ±2.0°C for dew point temperature 0°C at ambient temperature +25°C ±3.0°C for dew point temperature -10°C at ambient temperature +25°C ±6.0°C for dew point temperature -20°C at ambient temperature +25°C
Resolution	0.1 °C
MEASURING THE MOISTURE OF COMPRESSED AIR	
Measuring range	up to 25 bars
Air flow velocity	up to 25 m/s at a pressure of 1 bar (1m/s at a pressure of 25 bar)
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	1x connectable temperature+humidity probe
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Output	RS485
Range of humidity sensor temperature compensation	all temperature range

Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	ModBus RTU, ARION, Advantech ADAM
Power	9-30 Vdc
Protection class	IP65 electronics; IP40 sensors
Dimensions	88,5 x 114 x 39,5 mm; length/diameter of external probe 88/18 mm
External probe cable length	2 meters
Weight	approx. 210 g
Warranty	3 years