

WebSensor with PoE - remote CO2 concentration with Ethernet interface



code: T5640

CO2 - carbon dioxide t-line Web sensor with Power over Ethernet feature. Remote alarm.

Web Sensor with built-in concentration CO₂ sensor with PoE function.

A multiple point CO_2 and temperature adjustment procedure leads to excellent CO_2 measurement accuracy over the entire temperature working range; this is a must for process control and outdoor applications. The dual wavelength NDIR CO_2 sensing procedure compensates automatically for ageing effects. The CO2 module is highly resistant to pollution and offers maintenance free operation and outstanding long term stability.

The CO2 concentration is shown on the display or signaled by a color LED.

Processing and analysis of measured data:

- online in <u>COMET Cloud</u>
- <u>COMET Database</u> software
- integration into 3-party systems

Optional CO₂ measuring range extension from the standard 0 to 5,000 ppm up to 0 to 10,000 ppm (available at extra cost):

- Extended measuring range: 0 to 10 000 ppm
- Accuracy in extended range: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Technical data

| Range of CO2 concentration measurement | 0 to 5000ppm |
|---|--|
| Accuracy of CO2 concentration measurement | ±(50ppm +3% from reading) at 25°C and 1013hPa |
| Optional range of CO2 concentration measurement | 0 to 10000ppm ±(100ppm +5% from reading) at 25°C and 1013hPa |
| Resolution | 1ppm |
| Measuring interval | 15s |
| Temperature operating range | -20 to +60°C |
| IP protection | IP30 |
| LAN connection | RJ-45 connector, 10Base-T or 100Base-TX |
| Communication protocols | WWW, ModbusTCP, SNMPv1, SOAP, XML |
| Alarm protocols | E-mail, SNMP Trap, Syslog |
| Configuration | T-Sensor, WWW configuration |
| Power | Power over Ethernet according to IEEE 802.3af or 5Vdc |
| Power connector | co-axial, diameter 5.5 x 2.1mm |
| Dimensions | 136 x 136 x 45mm (W x H x D) |

| Weight | approximately 300g |
|----------|--------------------|
| Warranty | 3 years |