# Industrial temperature, humidity, bar. pressure transmitter - RS232 output, cable 2 meters



code: T7311-2

Temperature, humidity, atmospheric pressure transmitter. Outdoor, indoor use.
Humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy. Built-in pressure sensor.

The device is supplied with T+RH probe with 2 meters cable.

## Technical data

| | |
|---|---|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +105 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 0 to 100 % RH |
| Accuracy | ±2.5 % RH from 5 to 95 % at 23 °C |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -60 to +80 °C |
| Accuracy | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution | 0.1 °C |
| ATMOSPHERIC PRESSURE SENSOR SENSOR | |
| Measuring range | 600 to 1100 hPa |
| Accuracy | ±1.3 hPa at 23 °C from 800 to 1100 hPa |
| Resolution | 0.1 hPa |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +80 °C |
| Channels | internal atmospheric pressure sensor, 1x connectable temperature+humidity probe |
| Counted values | dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy |
| Output | RS232 |
| Range of humidity sensor temperature compensation | all temperature range |
| Available temperature units | degrees Celsius, degrees Fahrenheit |
| Communication protocol | ModBus RTU and Advantech ADAM compatible protocol |

| | |
|---|---|
| Power | 9-30 Vdc |
| Protection class | IP54 electronics; IP40 sensors |
| Dimensions | 88,5 x 114 x 39,5 mm; length/diameter of external probe 88/18 mm |
| External probe cable length | 2 meters |
| Weight | approx. 210 g |
| Warranty | 3 years |