

Sensor for One Digital Temperature and Humidity or CO2 Probe, with Internal Barometric Pressure Sensor, Ethernet Output and PoE

code: TA7611



The TA7611 extends the capabilities of the TA3611 model with integrated atmospheric pressure measurement. The device allows for the connection of one digital probe for temperature and humidity or CO2 measurement, while pressure is measured internally.

Thanks to the combination of an external probe and an internal pressure sensor, the TA7611 is suitable for applications where multiple environmental parameters must be monitored while maintaining a compact design. Naturally, it features an LCD display, multi-level alarm signaling, and PoE support.

The device is unique for meteorological applications or laboratories where conditions in a chamber (external probe) and ambient pressure must be measured simultaneously.

With the 'option' function, the device can also read temperature and pressure measured by the CO2G-10 probe if enabled.

Main Benefits:

- External T+RH or CO2 probe + internal atmospheric pressure sensor
- Backlit LCD display, acoustic and LED alarm signaling
- Power supply 5-24 V or PoE
- Integrated backup memory
- Modern web interface, IPv4/IPv6 support, Modbus TCP, COMET Cloud, and fully encrypted communication (HTTPS, SNMPv3, TLS)
- Integrated detachable bracket for easy installation

Technical data

| | |
|-----------------------------|---|
| TEMPERATURE SENSOR | |
| Measuring range | Depending on the connected DSxx probe |
| Accuracy | Depending on the connected DSxx probe |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | Depending on the connected DSxx probe |
| Accuracy | Depending on the connected DSxx probe |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | Depending on the connected DSxx probe |
| Accuracy | Depending on the connected DSxx probe |
| Resolution | 0.1 °C |
| ATMOSPHERIC PRESSURE SENSOR | |
| Measuring range | 600 to 1100 hPa |
| Accuracy | $\pm(1.3 \text{ hPa} + 0.06\% \text{ of configured output range})$ at 23 °C, from 800 to 1100 hPa |
| Resolution | 0.1 hPa |

| | |
|--------------------------------------|---|
| CO2 SENSOR | |
| Measuring range | 0 to 10,000 ppm |
| Accuracy | ±(100 ppm + 5% of reading) at 23 °C and 1,013 hPa |
| Resolution | 1 ppm |
| CO2 probe cable length | 1, 2 or 4 meters |
| GENERAL TECHNICAL DATA | |
| Operating temperature range | -30 to +60 °C |
| Measurement channels | integrated atmospheric pressure sensor, 1× combined T+RH probe (cable-mounted) or CO ₂ probe, ELKA connector |
| Calculated values | dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy, humidex, heat index |
| Supported temperature units | degrees Celsius (°C), degrees Fahrenheit (°F) |
| Supported atmospheric pressure units | hPa, kPa, mbar, mmHg, inHg, inH2O, PSI, oz/in2 |
| Power supply | Power over Ethernet (IEEE 802.3af) or 5-24 V DC |
| Network interface | Ethernet |
| IP support | IPv4, IPv6 |
| Communication protocols | HTTP(s), Web server (WWW), HTTP GET (JSON, XML), Modbus TCP, SNMPv1, SNMPv2c, SNMPv3 |
| Alarm protocols | Email (SMTP), Syslog |
| Measurement interval | 2 s |
| Ingress protection (IP rating) | IP30 (electronics) |
| Dimensions | 116 × 85 × 42 mm (without connected probe) |
| Weight | 240 g |
| Warranty | 3 years |