IoT Wireless Temperature Datalogger for 2 external probes, with two two-state inputs, built-in 2G modem and Flat Rate SIM Card

code: U0843Msim

IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud.

GSM Datalogger is designed to record from two external temperature probes and two two-state inputs. In case of exceeded set limits e-mail is sent from the COMET Cloud.

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.
The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard.**

With a newly purchased IoT wireless datalogger with a built-in modem, you receive 3 months of COMET Cloud for free; a full year of operation in COMET Cloud then requires 1 credit.

Technical data

TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-200 to +260 °C
Accuracy	±0.2°C; ±0,2 % of the measurement value in a range of +100 to +260 °C
Resolution	0.1 °C
Response time t90 of temperature measurement (temperature step 20°C, air flow approximately 1m/s)	according to the connected probe
BINARY INPUT	
Parameters of the voltage contact	„L“ level input voltage:< 0,4 V(*); „H“ level input voltage:> 2 V; Minimum voltage applicable:0 V; Maximum voltage applicable:+30 V DC
Parameters of the voltage-free contact	Contact resistance in „switched-on“ state:< 10 kOhm; Contact resistance in the „switched-off“ state:> 300 kOhm; Contact voltage in the „switched-off“ state:ca 3 V; Minimum state duration necessary for latching the state:1s
GSM MODEM PARAMETERS	
Quad-band	850/900/1800/1900MHz
Compliant to GSM	Phase2/2+
GPRS	GPRS mobile station class B
Class 4	2W @ 850/900MHz
Class 1	1W @ 1800/1900MHz
GENERAL TECHNICAL DATA	
Operating temperature	-20 to +60 °C
Channels	2x external temperature probe, 2x binary input

Memory	500,000 values in noncyclic logging mode; 350,000 values in cyclic record mode
Recording interval to the internal memory	adjustable from 1 second to 24 hours
Recording interval to the COMET Cloud	from 5 minutes
Interval for measuring and evaluating alarms	adjustable 1 s, 10 s, 1 min
Recording mode	noncyclic - data logging stops after filling the memory cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	rechargeable Li-Ion battery A8200, 3.6V/5200mAh
Protection class	IP20
Dimensions	61 x 93 x 53 mm, with antenna 120 x 93 x 53 mm
Weight (including batteries)	approx. 270 g
Warranty	3 years